

[54] SAFETY DEVICE MORE PARTICULARLY
FOR RABBIT OF DOOR

[76] Inventor: Marceau Ippolito, Lot 55, Rue des
Tiamas, Abidjan, Ivory Coast

[21] Appl. No.: 593,315

[22] Filed: July 7, 1975

[30] Foreign Application Priority Data

Aug. 13, 1974 France 74.27992

[51] Int. Cl.² E05D 11/00

[52] U.S. Cl. 16/137; 16/148;
49/383

[58] Field of Search 16/137, 148; 49/383,
49/486, 475

[56] References Cited

U.S. PATENT DOCUMENTS

465,708 12/1891 Bishop 16/137

474,633	5/1892	Glazier	49/383
613,592	11/1898	Nagley	49/383
1,444,398	2/1923	Shepherd	49/383 X
1,626,844	5/1927	Kuhn	49/383 X
2,641,792	6/1953	Peeler	16/137
2,694,234	11/1954	Roby et al.	49/383
3,581,884	6/1971	Caldwell	49/486 X

Primary Examiner—Andrew V. Kundrat

[57] ABSTRACT

A safety device for covering the groove of an opening between doors, windows and the like, and its surrounding casing. The device comprises a bellows mounted opposite to the hinge axis whose opened out folds cover the groove when the door is open and which folds upon one another and to the door itself when the latter is closed.

6 Claims, 4 Drawing Figures

